

Konveksne kape

Standard: DIN 28011

Materijal: St 37.0 - St 35.8

Uverjenje o kvalitetu: 2.2 - 3.1.B

Spoljni prečnik mm	Debljina S mm	Visina H mm	Visina stranice h	Duži radijus R	Kraći radijus r
21.3	2	12	4	21	4
26.9	2	14	5	27	4
33.7	2.3	17	5	34	4
42.4	2.6	20	5	43	4
48.3	2.6	21	6	48	4
60.3	2.9	25	7	60	6
70	2.9	28	8	70	6
76.1	2.9	30	9	76	6
88.9	3.2	33	11	89	8
101.6	3.6	34	11	102	8
108	3.6	35	11	108	8
114.3	3.6	36	12	114	8
133	4	39	12	133	10
139.7	4	41	12	140	12
159	4.5	51	15	159	15
168.3	4.5	56	16	168	15
193.7	5.4	57	17	194	20
219.1	6.3	57	17	220	20
244.5	6.3	60	17	240	25
273	6.3	70	18	270	38
323.9	7.1	87	35	324	32
355.6	8	89	40	355	35
368	8	95	40	368	37
406.4	8.8	99	45	406	41
419	8.8	105	45	419	42
457.2	10	110	50	460	46
508	10	120	50	508	51

