


Koncentrične redukcije

Standard: DIN 2616

Materijal: St 37.0 - St 35.8

Uverenje o kvalitetu: 2.2 - 3.1.B



Dimenzije			Ø Dimenzije			Visina H mm	Tolerancije	
inch	D mm	Debljina S mm	inch	d mm	Debljina s mm		Visina H mm	Debljina S mm
3/4	26.9	2.3	1/2	21.3	2.0	38	±2.5	Ne manje od 87.5% debljine
1	33.7	2.6	1/2	21.3	2.0	50		
			3/4	26.9	2.3			
1 1/4	42.4	2.6	1/2	21.3	2.0	50		
			3/4	26.9	2.3			
			1	33.7	2.6			
1 1/2	48.3	2.6	3/4	26.9	2.3	64		
			1	33.7	2.6			
			1 1/4	42.4	2.6			
2	60.3	2.9	3/4	26.9	2.3	76		
			1	33.7	2.6			
			1 1/4	42.4	2.6			
			1 1/2	48.3	2.6			
2 1/2	76.1	2.9	1	33.7	2.6	90		
			1 1/4	42.4	2.6			
			1 1/2	48.3	2.6			
			2	60.3	2.9			
3	88.9	3.2	1 1/4	42.4	2.6	90		
			1 1/2	48.3	2.6			
			2	60.3	2.9			
			2 1/2	76.1	2.9			
4	114.3	3.6	1 1/2	48.3	2.6	100		
			2	60.3	2.9			
			2 1/2	76.1	2.9			
			3	88.9	3.2			
5	139.7	4.0	2	60.3	2.9	127		
			2 1/2	76.1	2.9			
			3	88.9	3.2			
			4	114.3	3.6			
6	168.3	4.5	2 1/2	76.1	2.9	140		
			3	88.9	3.2			
			4	114.3	3.6			
			5	139.7	4.0			
8	219.1	6.3	4	114.3	3.6	152		
			5	139.7	4.0			
			6	168.3	4.5			
10	273.0	6.3	4	114.3	3.6	178		
			5	139.7	4.0			
			6	168.3	4.5			
			8	219.1	6.3			
12	323.9	7.1	6	168.3	4.5	203		
			8	219.1	6.3			
			10	273	6.3			

Dimenzije			Ø Dimenzije		Visina H mm	Tolerancije	
inch	D mm	Debljina S mm	d mm	Debljina s mm		Visina H mm	Debljina S mm
14	355	8	323.9	7.1	330	±5	Ne manje od 87.5% debljine
			273	6.3			
			267	6.3			
			219.1	6.3			
368	8	323.9	7.1				
		273	6.3				
		267	6.3				
		219.1	6.3				
		168.3	4.5				
			159	4.5	355		
406.4	8.8	368	8				
		355.6	8				
		323.9	7.1				
		273	6.3				
		267	6.3				
			219.1	6.3	355		
419	10	368	8				
		355.6	8				
		323.9	7.1				
		273	6.3				
		267	6.3				
			219.1	6.3	381		
457	10	419	10				
		406	8.8				
		368	8				
		355.6	8				
		323.9	7.1				
		273	6.3				
267							
219.1							
20	508	11	470	10	508	±6	
			457	10			
			419	10			
			406	8.8			
			368	8			
			355.6	8			
			323.9	7.1	625		
			273	6.3			
			267	6.3			
			219.1	6.3			
22	610	11.5	521	11.5	350		
			508	11	490		
			457	10			
			419	10	575		
			406	8.8			
			368	8	675		
			355.6	8			
			323.9	7.1			